

Silicon PNP Power Transistors

2SB731

DESCRIPTION


- With TO-126 package
- Complement to type 2SD809
- Low collector saturation voltage

APPLICATIONS

- Audio frequency power amplifier
- Low speed switching

PINNING

PIN	DESCRIPTION
1	Emitter
2	Collector;connected to mounting base
3	Base

Absolute maximum ratings($T_a=25^{\circ}\text{C}$)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
V_{CBO}	Collector-base voltage	Open emitter	-60	V
V_{CEO}	Collector-emitter voltage	Open base	-50	V
V_{EBO}	Emitter-base voltage	Open collector	-6	V
I_C	Collector current (DC)		-1	A
I_{CM}	Collector current-Peak		-2	A
I_B	Base current (DC)		-0.5	A
P_T	Total power dissipation	$T_a=25^{\circ}\text{C}$	1.0	W
		$T_C=25^{\circ}\text{C}$	10	
T_j	Junction temperature		150	$^{\circ}\text{C}$
T_{stg}	Storage temperature		-55~150	$^{\circ}\text{C}$

Silicon PNP Power Transistors

2SB731

CHARACTERISTICS

T_j=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
V _{CEsat}	Collector-emitter saturation voltage	I _C =-1.0A; I _B =-50mA		-0.5	-0.6	V
V _{BEsat}	Base-emitter saturation voltage	I _C =-1.0A; I _B =-50mA		-1.0	-1.2	V
I _{CBO}	Collector cut-off current	V _{CB} =-50V; I _E =0			-0.1	μ A
I _{EBO}	Emitter cut-off current	V _{EB} =-6V; I _C =0			-0.1	μ A
h _{FE-1}	DC current gain	I _C =-0.1A ; V _{CE} =-2V	135		600	
h _{FE-2}	DC current gain	I _C =-1A ; V _{CE} =-1V	40			
f _T	Transition frequency	I _C =-10mA ; V _{CE} =-2V		75		MHz
C _{OB}	Collector output capacitance	I _E =0; f=1MHz ; V _{CB} =-10V		25		pF

◆ h_{FE-1} Classifications

L	K	F	E
135-270	200-400	300-480	360-600

Silicon PNP Power Transistors

2SB731

PACKAGE OUTLINE

